

### BATTERY STRAPPING TOOL FOR (PLASTIC STRAP) PP / PET DIGITAL CONTROL—FLAT AND ROUND SURFACES

#### TECHNICAL DATA :

Compact, versatile and easy to use battery powered strapping tool equipped with [two Li-ion Batteries and one charger](#). Manual, semi-automatic or automatic operation. Bosch brushless high torque motor for less wear and long life. High speed take-up. Standard and (soft) low tension mode. High impact reinforced casing with metal nose for drop damage resistance. Reinforced circuit board located in front of battery for improved protection. Perfect balance for reduced operator fatigue.

Strap Width	3/4" - 1.0" (19mm - 25mm)
Strap Thickness	0.030" to 0.050"
Max. Tension	1,000 lbs.
High Speed Take Up	6.1 inches / second
Weight	8.8 lbs. Including battery
Dimensions	6" H, 14" L, 4.5" W
Joint Type	Friction Seal
Battery	AKKU Power 18.0 V, 5.0 Ah Li-ion
Order Code MT 450	156.990.812



Manufactured by the Maillis Group

MAILLIS STRAPPING SYSTEMS—USA Inc. 404 Wall Street, Fountain Inn, SC 29644

Phone: 877-962-4648 / Fax: 864-409-3039 / Web: [maillisstrapping.com](http://maillisstrapping.com) / E-mail: [info@maillisstrapping.com](mailto:info@maillisstrapping.com)