

**BATTERY STRAPPING TOOL WITH FRICTION WELD SEAL FOR  
(PLASTIC STRAP) PP / PET  
DIGITAL CONTROL - FLAT AND ROUND SURFACES**

**TECHNICAL DATA :**

Compact, versatile and easy to use battery powered strapping tool equipped with two Li-ion Batteries and one charger. Manual, semi-automatic or automatic operation. Bosch brushless high torque motor for less wear and long life. High speed take-up. Standard and (soft) low tension mode. High impact reinforced casing with metal nose for drop damage resistance. Reinforced circuit board located in front of battery for improved protection. Perfect balance enhances vertical or horizontal use and reduced operator fatigue.

Strap Width	7/16", 1/2", 5/8"
Strap Thickness	.020" to .040"
Tension	725 lbs.
High Speed Take Up	10 inches / second
Weight	8 lbs. Including battery
Dimensions	6" H, 14" L, 4.5" W
Joint Type	Friction Weld Seal
Battery	AKKU Power 14.4 V, 4.0 Ah Li-ion
Order Code: MT-320	155.990.822 (When ordering indicate Black color if desired)
Package Type (Surface)	Flat (Min. 5" / 120mm) - Round (Min. 28" / 700mm)



Manufactured by the Maillis Group

MAILLIS STRAPPING SYSTEMS—USA Inc. 404 Wall Street, Fountain Inn, SC 29644

Phone: 877-962-4648 / Fax: 864-409-0367 / Web: [maillistrapping.com](http://maillistrapping.com) / E-mail: [info@maillistrapping.com](mailto:info@maillistrapping.com)

rev. 12/2019