

BATTERY STRAPPING TOOL WITH FRICTION WELD SEAL FOR (PLASTIC STRAP) PET DIGITAL CONTROL - FLAT AND ROUND SURFACES

TECHNICAL DATA :

Compact, versatile and easy to use battery powered strapping tool equipped with two Li-ion Batteries and one battery charger. Manual, semi-automatic or automatic operation. Ametek 36v brushless high torque motor for less wear and long life. Smooth, easy to control take-up. Standard and (soft) low tension mode. High impact reinforced casing with metal nose for drop damage resistance. Reinforced circuit board located in front of battery for improved protection. Perfect balance enhances vertical or horizontal use and reduced operator fatigue.

Strap Width	1.0" and 1-1/4" (25mm - 32mm)
Strap Thickness	0.031" to 0.051"
Tension	Min. (400 lbf. / 1800n) - max. (1,460 lbf. / 6500n)
High Speed Take Up	.656 inches / second
Weight	13.6 lbs. Including battery
Dimensions	7" H, 16.75" L, 5.5" W
Joint Type	Friction Weld Seal
Battery	AKKU Power 36 V, 5.0 Ah Li-ion
Order Code MT 650	164.990.811



Manufactured by the Maillis Group

MAILLIS STRAPPING SYSTEMS—USA Inc. 404 Wall Street, Fountain Inn, SC 29644

Phone: 877-962-4648 / Fax: 864-409-0367 / Web: maillisstrapping.com / E-mail: info@maillisstrapping.com